

Комплекът включва:

WC CERAMIC BAU Grohe without flange (without a trim) ceramic glazed (39427000)
SoftClose seat from Duroplast (39493000)
Solido support stand 113cm (38528001)
Arena Trigger Plate Chrome (38844000)
Sound insulation insert
Wall brackets (3855800M)

Frame Details:

For a flushing tank.
Horizontal output.
tank GD 2
Height: 1.13 m
for a load-bearing wall or a reinforced partition
steel frames epoxy finish
reinforced legs
Supplied with wall brackets for hollow partition, fully pre-assembled with quick adjustment and height lock up to 200 mm
supplied with fastening material
Supplied with rods and nuts to fix toilet bowl
ceramic fastening
pitch of fasteners 180/230 mm
drainage elbow from PP Ø 90 mm
adjustable to depth and height (200 mm)
reduction Ø 90/110 mm
drain and feed washer
tank 6 - 9 l
factory settings 3 and 6l
Pneumatic valve with 2 functions: double flushing or start / stop
side or rear feed
class silence I DIN 41 09
insulated anti-condensation tank
water supply with angular valve and flexible connection, quick connection without tools
control hatch:
- Build without tools
- closed during the construction phase
horizontal or vertical
with wall brackets (38,558,00M)

Технология:

RIMLESS technology: bacteria should not hide
Attention: The 90/100 reduction sleeve is ordered separately.
It is necessary to check the good condition of the packaging both outside and inside, at the time of delivery.
We have a 7-day period to claim a carrier.

GROHE

